Preliminary Amdt. dated December 13, 2005
Application Filing Date March 29, 2004

In the Claims:

1.   (Currently amended) A method for scenario synchronizing between a primary display and a secondary display of a communication device, comprising:

receiving an event at the communication device;

displaying information associated with the event on the secondary display;

retrieving additional information associated with the event from an application;

activating on the primary display an application that supports the event; and

displaying on the primary display the additional information associated with the event such that the additional information and functionality and information that is associated with the application are configured to be manipulated from in addition to the information displayed on the secondary display is accessible on the primary display when the primary display is accessed.

2.   (Original)   The method of Claim 1, wherein the communication device is a clamshell flip-style device.

3.   (Original)   The method of Claim 2, further comprising opening the communication device such that the primary display is accessible.

4.   (Original)   The method of Claim 1, wherein the event includes at least one of a task, a notification, an alert, and a user-activated application.

5.   (Original)   The method of Claim 1, further comprising dismissing the information associated with the event from the secondary display.

6.   (Currently amended) The method of Claim 1, further comprising manipulating interacting with the information associated with the event on the secondary display.

7.   (Currently amended) The method of Claim 1, further comprising manipulating interacting with the additional information associated with the event on the primary display.

8.   (Currently amended)   A system for scenario synchronizing in a communication device, comprising:

a secondary display;

a primary display coupled to the secondary display; and

an application that activates upon the occurrence of an event at the communication device, wherein:

information associated with the event is retrieved from the application and displayed on the secondary display, and wherein

additional information associated with the event and functionality and information associated with the application are configured to be manipulated from in addition to the information displayed on the secondary display is accessible on the primary display when the primary display is accessed.

9.   (Original)   The system of Claim 8, wherein the primary display is larger than the secondary display.

10.   (Original)   The system of Claim 8, wherein the secondary display is located on an outer surface of the communication device.

11.   (Original)   The system of Claim 8, wherein the communication device is a clamshell flip-style device.

12.   (Original)   The system of Claim 11, wherein the primary display is accessible when the communication device is opened.

13.   (Original)   The system of Claim 8, wherein the event includes at least one of a task, a notification, an alert, and a user-activated application.

14.   (Original)   The system of Claim 8, further comprising a first set of hardware coupled to the secondary display for manipulating content shown on the secondary display.

15.   (Original)   The system of Claim 8, further comprising a second set of
hardware coupled to the primary display for manipulating content shown on the primary display.

16.   (Currently amended)   A computer-readable medium on which is stored a
computer program for scenario synchronizing between a primary display and a secondary display
of a communication device, the computer program comprising instructions, which when
executed by a computer, perform:
   receiving an event at the communication device;
   displaying information associated with the event on the secondary display;
   retrieving additional information associated with the event from the application;
   ~~activating on the primary display an application that supports the event;~~ and
   displaying on the primary display the additional information associated with the event
such that the additional information and functionality ~~and information~~ that is associated with the
application are configured to be manipulated from ~~in addition to the information displayed on the
secondary display is accessible on~~ the primary display when the primary display is accessed.

17.   (Original)   The computer-readable medium of Claim 16, further comprising
dismissing the information associated with the event on the secondary display.

18.   (Original)   The computer-readable medium of Claim 16, wherein the event
includes at least one of a task, a notification, an alert, and a user-activated application.

19.   (Original)   The computer-readable medium of Claim 16, wherein the
communication device is a clamshell flip-style device.

20.   (Currently amended)   A system for scenario synchronizing between a primary
display and a secondary display of a communication device, comprising:
   means for receiving an event at the communication device;
   means for displaying information associated with the event on the secondary display;
   means for retrieving additional information associated with the event from the
application;

Preliminary Amdt. dated December 13, 2005
Application Filing Date March 29, 2004

means for activating on the primary display an application that supports the event; and

means for displaying on the primary display the additional information associated with the event such that the additional information and functionality and information that is associated with the application are configured to be manipulated from in addition to the information displayed on the secondary display is accessible on the primary display when the primary display is accessed.

Page 5 of 6